

Konfigurace telefonem

Některé příkazy mohou být zadány prostřednictvím analogového telefonu připojeného k VoIP bráně přes „Phone“ vstup.

```
***** Reboot/Restart VoIP brány  
**100 VoIP brána pracuje ve STATIC módu  
**101 VoIP brána pracuje v DHCP módu  
**111 Získej IP adresu brány hlášením (po anglicky)  
**222 Získej VoIP telefonní číslo brány hlášením
```

IP brána je nastavená na DHCP.

Uživatelské jméno a heslo je **admin**

**V případě ztráty hesla do brány je nutné bránu restartovat přes telnet.
Postup zašleme na požádání e-mailem.**

VoIP IP 012B-2

SIP Configuration

Current State

Network

VOIP

Advance

Dial-peer

Config Manage

Update

System Manage

SIP Setting

Po správném nastavení čísla bude Status Registered

Register Status	Unregistered	Proxy Server Addr	<input type="text"/>
Register Server Addr	aps.sbohempevnalinko.	Proxy Server Port	<input type="text"/>
Register Server Port	5060	Proxy Username	<input type="text"/>
Register Username	Vaše VOIP číslo	Proxy Password	<input type="text"/>
Register Password	Heslo k číslu	Local SIP Port	5060
Domain Realm	aps.sbohempevnalinko.	Register Expire Time	120 seconds
Phone Number	Vaše VOIP číslo	RFC Protocol Edition	RFC3261
Detect Interval Time	120 seconds	Server Type	common
Encrypt Key	<input type="text"/>	User Agent	Voip Phone 1.0
DTMF Mode	DTMF_RFC2833	CLIR	Disable
Enable PRACK	<input checked="" type="checkbox"/>	Signal Encrypt	<input type="checkbox"/>
Auto Detect Server	<input type="checkbox"/>	Rtp Encrypt	<input type="checkbox"/>
Enable Keep Authentication	<input checked="" type="checkbox"/>	Enable Session Timer	<input type="checkbox"/>
Enable Via rport	<input checked="" type="checkbox"/>	Answer With Single Codec	<input type="checkbox"/>
Enable DNS Srv	<input type="checkbox"/>	SIP(Default Protocol)	<input checked="" type="checkbox"/>
Enable Register	<input checked="" type="checkbox"/>		
<input type="button" value="Apply"/>			

VoIP IP 012B-2

- Current State
- Network
- VOIP
- Advance
- Dial-peer
- Config Manage
- Update
- System Manage

WAN Configuration

Active Status

Active IP	192.168.1.53
Current Netmask	255.255.255.0
MAC Address	00:0d:19:02:0f:ea
Current Gateway	192.168.1.254
Mac Authenticating Code	Valid MAC

Static Mode Setting

IP Address	192.168.1.179	Netmask	255.255.255.0
Gateway	192.168.1.1	DNS Domain	
Primary DNS	202.96.134.133	Alter DNS	202.96.128.68

NET Mode Setting

Static <input checked="" type="radio"/>	DHCP <input type="radio"/>	PPPOE <input type="radio"/>	
---	----------------------------	-----------------------------	--

PPPoE Mode Setting

PPPOE Server	ANY
Username	user123
Password	*****

Apply

Jestli se jedná o STATIC - statické připojení, požádejte Vášho poskytovatele internetu o IP adresu, masku podsítě, výchozí bránu, DNS server, případně náhradní DNS server. Údaje vpište zde...

IP brána je z výroby nastavená na DHCP. Jestli máte dynamické připojení k internetu, nic víc nevpisujete.

VoIP IP 012B-2

DSP Configuration

DSP Set:			
Coding Rule	g711Alaw64k	Signal Standard	CZECH
Input Volume	2 (0-3)	Output Volume	2 (0-3)
G729 Payload Length	10 ms	DTMF Payload Type	101
iLBC Payload Type	97 (96-127)	iLBC Payload Length	30 ms
CallerID Tx Mode	FSK	Fax Mode	BYPASS-A
Flashhook Min Time	200 ms	Flashhook Max Time	400 ms
<input type="checkbox"/> VAD			
<input type="button" value="Apply"/>			

VoIP IP 012B-2

Current State

Network

VOIP

Advance

Dial-peer

Config Manage

Update

System Manage

Running Status

Network

WAN		LAN	
Connect Mode	DHCP	IP Address	192.168.10.1
MAC Address	00:0d:19:02:0f:ea	DHCP Server	ON
IP Address	192.168.1.53		
Gateway	192.168.1.254		

VOIP

Default Protocol:SIP			
SIP		IAX2	
Register Server	81.91.216.18	IAX2 server	
Proxy Server	81.91.216.18	Register	OFF
Register	ON	State	Unregistered
State	Unregistered <i>Registered</i>		
SIP STUN	OFF		

Phone Number

Public SIP	
Private SIP	
IAX2	

Version: VOIP Gateway V1.6.64.15 Jan 11 2008 12:22:38

*Jestli je IP brána registrovaná, v položce STATE se Vám zobrazí REGISTERED a na zařízení Vám bude trvale svítit zeleným REG.
 Pokud je zařízení neregistrované, v položce STATE najdete UNREGISTERED a REG Vám bude blikat.*

VoIP IP 012B-2

Vždy ještě jednou uložit:



The screenshot shows a web interface with a blue sidebar on the left and a main content area on the right. The sidebar contains the following menu items: Current State, Network, VOIP, Advance, Dial-peer, Config Manage, Update, and System Manage. The main content area has a title 'Save Configuration' and a dialog box titled 'Save All'. The dialog box contains the text 'Press the "Save" button to save the configuration files !' and a 'Save' button.

Aktualizace firmwaru:



The screenshot shows a web management interface for a device. On the left is a blue sidebar with a menu containing the following items: Current State, Network, VOIP, Advance, Dial-peer, Config Manage, Update (highlighted with a red underline), and System Manage. The main content area has a light gray background and is titled "Web Update" in blue text. Below the title is a section titled "Update Option" with a blue header. This section contains a "Select file" label, a text input field with a "Procházet..." button and a file type filter "(*.dlf or *.cfg)", a warning message "The device will reboot when update finish!", and an "Update" button.